

# HECO®

**DIREKT**  
*Dreiklang*



# HECO®

**DIREKT**  
*Dreiklang*



# HECO®

**DIREKT**  
*Dreiklang*



White & Silver



Black & Black

# HECO®

## DIREKT *Dreiklang*



## HIGHLIGHTS

### High-end high-efficiency three-way floor-standing loudspeakers

- Very large three-way system with particularly high efficiency for outstanding dynamics
- Can be combined optimally with transistor and tube amplifiers from 20 watts per channel
- Attractive flat-design enclosure, floating appearance through all-metal design foot construction

#### Drivers

- High-power tweeter with particularly high efficiency through the 28 mm silk compound cone, solid aluminium front panel with high-efficiency wave-control horn geometry and powerful triple magnet system
- Especially efficiency and gentle roll-off-optimized midrange with Kraft paper cone, lightweight dust-protection cone, hard suspension, very powerful drive, extremely low-loss silk surround and highly durable voice coil in a stable die-cast aluminium cage. Kapton voice-coil and impedance compensation for extremely low mechanical and electrical loss
- High-performance woofer with high-capacity 75 mm 4-layer voice coil and lightweight air-dried Ripple cone in a very stable die-cast aluminium cage. Kapton voice coil, ventilated pole core, low-loss rubber surround and extremely powerful 170 mm magnet system for minimum loss and excellent dynamics
- Woofer and midrange: Magnet systems linearized with the high-tech Klippel® measuring system for ideal symmetry and minimal distortions

#### Cabinet

- Stylish semi-matt lacquer finish with contrasting double stripes on the front
- Solidly built, multiple strutted MDF flat enclosure with attractive curves
- Specially designed all-metal foot construction for an absolutely stable base
- Floor-protecting rubber feet and all-metal spikes included
- Triple bass-reflex design with bi-directional airflow-optimized rounded downfire tubes for maximum bass performance

#### Crossover

- Elaborate, phase-optimized crossover with high-quality tight-tolerance components
- Linearized impedance curve with very little fluctuation for optimum behavior on tube and transistor amplifiers from 20 watts per channel
- High-quality all-metal connector terminal with stable, gold-plated high-end screw terminals

# HECO®

**DIREKT**  
*Dreiklang*

## Direkt Dreiklang

### Principle Equipment

3-way bass reflex  
15" Woofer  
8" Midrange  
1.2" Dome-tweeter

### Power Handling (RMS/Max)

350/600 W

### Impedance

4 - 8  $\Omega$

### Frequency Response

19 - 30 000 Hz

### Crossover Frequencies

200 Hz/3 100 Hz

### Recommended Amplifier Output

20 - 600 W

### Sensitivity

98 dB

### Cabinet surface

Black & Black, White & Silver

### Dimensions (WxHxD)

Cabinet 700 x 1150 x 320 (350 incl. Terminal) mm

Incl. Metal spikes 700 x 1235 x 515 mm

### Weight

68.4 kg

Black & Black  
White & Silver

Art. No. 135 0710 EAN: 40 29678 50710

Art. No. 135 0712 EAN: 40 29678 50712

