



# POWER STAR SPEAKER SERIES

**POWER STAR 2.16**



**POWER STAR 2.13**



**POWER STAR 69.3**



**POWER STAR 16.2**



**POWER STAR 13.2**



**POWER STAR 10.2**



## HIGHLIGHTS

- Solid steel basket including additional voice-coil ventilation
- Polypropylene cone with titanium hairline finish
- Long excursion rubber surround
- Titanium-coated tweeter/midrange cone (69.3)

- Mac Audio design magnet protection cover
- Suspension and magnetic field optimised with KLIPPEL® measurement system
- Solid hexagon protection cover with aluminium diamond-cut logo
- Titanium tweeter (2.16/2.13)/ Titanium-coated tweeter cone
- External XO including PTC tweeter protection circuit (2.16/2.13)

SPECIFICATIONS	Power Star 2.16	Power Star 2.13	Power Star 69.3	Power Star 16.2	Power Star 13.2	Power Star 10.2
Principle	2-way	2-way	3-way	2-way	2-way	2-way
System	compo	compo	triaxial	coaxial	coaxial	coaxial
Power handling RMS/max. (W)	100/400	80/320	120/480	100/400	80/320	60/240
Impedance (Ω)	4	4	4	4	4	4
Frequency response (Hz)	30 - 26 000	34 - 26 000	28 - 24 000	30 - 24 000	34 - 24 000	38 - 24 000
Crossover frequencies (Hz)	3 800	3 800	2 800/4 200	4 200	4 200	4 200
SPL (dB)	90	90	91	90	90	89
DIN-Ø (mm)	165 W/19 T	130 W/19 T	6x9" /0.5" /2"	165 W/13 T	130 W/13 T	100 W/13 T
Cutting Out (mm)	142 W/38 T	113 W/38 T	221 x 151	142	113	94
Mounting depth (mm)	57 W/ 17 T	51 W/ 17 T	78	57	51	50
Art.No.	110 5726	110 5723	110 5719	110 5716	110 5713	110 5710
EAN.	40 23037 05726 3	40 23037 05723 2	40 23037 05719 5	40 23037 05716 4	40 23037 05713 3	40 23037 05710 2