

MAC AUDIO

WRS



WRS 16.2



WRS 13.2



HIGHLIGHTS

- 2 way coaxial speaker
- Specially designed for applications in the maritime sector and damp locations
- Water resistant according to standard IPX 6
- UV resistant according to standard ASTM-D4329
- Salt water resistant according to standard ASTM-B117
- Solid ABS basket
- Internal high-power ferrite magnet system
- Dynamic surround for high efficiency
- Coated polypropylene cone (woofer)
- Integrated design speaker grille

Specifications	WRS 16.2	WRS 13.2
Principle	2 way coax system	2 way coax system
System	70/250	60/200
Power handling RMS/max. (W)	8	8
Impedance (Ω)	28 – 24.000	32 – 24.000
Frequency response (Hz)	3800	3800
Crossover frequencies (Hz)	91	90
SPL (dB)	Woofer 165	Woofer 130
DIN-Ø (mm)	Woofer 179	Woofer 147
Cutting Out (mm)	Woofer 131	Woofer 111
Mounting depth (mm)	Woofer 60	Woofer 48
Mounting Height (mm)	Woofer 23	Woofer 19
Membran Material	Woofer: coated polypropylene cone, tweeter: polycarbonate	
Art.No.	133 3060	133 3050
EAN.	40 23037 33060 1	40 23037 33050 2