







Designation	Art. No.	Unit	Colour
Black Magic 40	92449	0.4 m	black
Black Magic 75	92450	0.75 m	black
Black Magic 120	92451	1.2 m	black
Black Magic 170	92453	1.7 m	black
Black Magic 220	92454	2.2 m	black
Black Magic 320	92455	3.2 m	black
Black Magic 510	92456	5.1 m	black
Black Magic 750	92457	7.5 m	black
Black Magic 1000	92458	10 m	black

CONNECTIONS	SIGNAL TYPE		SIGNAL DIRECTION
2000000000 200000000000000000000000000	((()		;—;
HDMI HDMI	Audio	Video	Bi-Directional

IN 🕒

PLASMA / LCD | PROJECTOR

OUT \square

DVD PLAYER | HDD RECORDER | SAT RECEIVER | DVD RECORDER

Black Magic

High Speed HDMI cable with ethernet

This high-speed HDMI® cable delivers unlimited home-cinema fun. The additional data channel (Ethernet channel) allows Internet-enabled AV components, e.g. Blu-ray players and AV receivers, to be connected without the need for additional network cables. The high-quality inner conductor, which is manufactured from OFC copper and features triple shielding as well as 24-carat gold-plated plug contacts, guarantees the transmission of completely stable and interference-free signals – particularly where critical digital signals are concerned.

Features

- ✓ 4K Ultra HD at 50/60 Hzxxx
- √ 18 GBit/s data rate
- √ 21:9 cinema image format
- ✓ 5.1 DTS HD
- ✓ Dolby True HD
- ✓ ARC Audio Return Channel
- √ 32 digital audio channels
- √ 24- carat gold-plated contacts
- ✓ 3D TV at 4 K resolution
- ✓ CEC 2.0
- ✓ 30/36/48-bit Deep Color
- √ High-Speed-HDMI®-cable
- ✓ Full HD Video
- ✓ x.v.Color Additional Color Space
- ✓ triple shielding
- ✓ Robust plastic sheathing
- ✓ OFC oxygene free copper
- ✓ HDMI CEC Automated A/V Control
- $\checkmark~\text{HEC}$ $\text{HDMI}^{\text{\tiny{\$}}}$ with Ethernet channel
- ✓ Ultra HD

Technical Data

Resolution 4K + 2K - 2160p/ 60 Hz**Inner conductor material** 0FC -oxygene free copper

Cable sheathing plastic
Shielding quantity triple shielding

Shielding material 2 x aluminium foil + 1 x copper braid

Cable geometry Round Plug type Straight

Plug material Enclosed plastic plug































