



QUALITY ★★★★★





| Designation | Art. No. | Unit | Colour |
|----------------|----------|--------|--------|
| Series 1 X 50 | 13130 | 0.5 m | Blue |
| Series 1 X 200 | 13136 | 2 m | Blue |
| Series 1 X 175 | 13135 | 1.75 m | Blue |
| Series 1 X 75 | 13131 | 0.75 m | Blue |
| Series 1 X 100 | 13132 | 1 m | Blue |
| Series 1 X 125 | 13133 | 1.25 m | Blue |
| Series 1 X 150 | 13134 | 1.5 m | Blue |

CONNECTIONS

XLR Cou-

XLR Plug



SIGNAL TYPE

₩

SIGNAL DIRECTION



LF audio cable with XLR plug, symmetrical layout

Particularly high-quality analogue audio cable with symmetrical design and effective triple shielding for cabling hi-fi and home-cinema systems! The silver-plated inner conductor made from oxygen-free copper (SPC = silver-plated copper) means that this Oehlbach cable delivers particularly good spatiality and outstanding dynamics. Perfect contact reliability and a pleasant handling are guaranteed with the 24-carat gold-plated contacts. The cable may be used for all purposes and is absolutely resistant to all sheath currents thanks to its extremely flexible outer sheath and metal plug. There is nothing to stand in the way of the robust deployment of these cables as they also come preassembled with locking XLR plugs.

Features

- \checkmark HPOCC $^{\scriptscriptstyle (\! B\!)}$ mono-crystalline oxygen-free copper inner conductor
- ✓ 24- carat gold-plated contacts
- ✓ Plug with automatic lock
- ✓ triple shielding
- ✓ Robust plastic sheathing
- ✓ Solid full-metal plug
- ✓ Symmetrical cable layout
- ✓ inner conductor: twisted pair
- ✓ Reliable contact
- ✓ Made in Germany

Technical Data

| Inner conductor material | HPOCC [®] - monocristalline copper | |
|--------------------------|---|--|
| Cable sheathing | plastic | |
| Shielding quantity | triple shielding | |
| Shielding material | 2 x aluminium foil + 1 x copper braid | |
| Plug design | Full-metal screw-type plug | |
| Special length | Also available in individual customised lengths | |
| Cable geometry | Round | |
| Plug type | Straight | |
| Capacity | 45 pF/m | |
| | | |
| | | |

100% Contact

24 ct

Twisted Pair HP

3x Shielding

pling

Bi-Directional

