



BLK 1000/4000

BLK 1000



BLK 4000



HIGHLIGHTS

- Variable Bass Boost 0-12dB at 45 Hz
- Multi Connectivity: High and low level inputs
- Automatic turn on/off remote output for subwoofer amplifier
- Adjustable input sensitivity
- Low level RCA outputs providing signal from the rear channels for use with a subwoofer amplifier
- Multi Connectivity: High and low level inputs
- Variable Low- and Highpass filters 25 Hz - 200 Hz (12dB per Octave)

| SPECIFICATIONS | BLK 1000 | BLK 4000 |
|--|----------------------------------|----------------------------------|
| Typ | 1-Channel Class D Mini Amplifier | 4-Channel Class D Mini Amplifier |
| Max. power output (sine burst 2:8, 1 kHz) into 4 ohms , 14.4V | 360 W | 4x 100 W |
| RMS power output (DIN 45 324) into 4 ohms, 14.4V | 180 W | 4x 50 W |
| Max. power output (sine burst 2:8, 1 kHz) into 2 ohms , 14.4V | 600 W | 4x 160 W |
| RMS power output (DIN 45 324) into 2 ohms, 14.4V | 300 W | 4x 80 W |
| Frequency response | 15 Hz – 250 Hz (-3 dB) | 10 Hz – 30 kHz (-3 dB) |
| THD | < 0,05 % (1 kHz) | < 0,05 % (1 kHz) |
| Signal-to-noise ratio (A-weighted) | > 100 dB | > 100 dB |
| Input sensitivity low level inputs | 0,2 V – 6 V | 0,2 V – 6 V |
| Input sensitivity high level inputs | 0,6 V – 8 V | 0,6 V – 8 V |
| Input impedance low level inputs | 100 kOhm | 100 kOhm |
| Input impedance high level inputs | 1 kOhm | 1 kOhm |
| Power supply | 12 V minus an Masse | 12 V minus an Masse |
| Dimensions (W x H x D) | 172 x 36 x 97 mm | 172 x 36 x 97 mm |
| Amplifier Weight | 0,58 kg | 0,65 kg |
| Art.No.: | 110 3772 | 110 3774 |
| EAN. | 40 23037 03772 2 | 40 23037 03774 6 |